

X-Treme Collection Specification & Maintenance For Oiled Floors

2-Ply Multilayer plank with 6 mm top layer of veneer glued on to 15 mm birch plywood. Bevelled on 4 - 4 sides.

Treated with 2 coats of hard wax and oil. Or generally 5 coats of UV lacquer

Can be floated, glued or nailed direct onto subfloor or nailed directly onto joists.

Sapwood on face side allowed till 10% of the boards

All packages to be stored in a secure & dry area, packages must never be directly on a cement floor, recommended storage temperature is 15deg, (not in a cold or hot environment and never outdoors) relative humidity should be between 40 and 60%, do not open packages until ready to be installed, open & lay one pack at a time.

- Cracks allowed
- Knots allowed (no maximum)
- Tongued and grooved on 4 sides

Quality: 21 mm with 6mm wear layer

Overall Thickness: 21 mm (bevelled)

Length: 1830-1860mm
Single Strip (Plank)

Board Width: 189mm
Single Strip (Plank)

Pack Size: 1.406 m² per pack (4 panels)

Maintenance for Xylo X-Treme Oiled Hardwood Flooring:

Application instructions:

The oil which is applied to the surface of the flooring will protect against both soiling and moisture ingress. You will also find that an oiled floor shows scratching to a far lesser degree than a lacquered timber floor.

The flooring has been oiled at the time of manufacture. The oil does however tend to dry out over a period of time and in consequence your flooring will require an occasional coat of oil in order to keep it looking at it's best.

This is a simple procedure and can be applied by the end user. Simply brush a coat of maintenance oil sparingly onto the surface of the timber floor and allow it sufficient time to dry. In the average home we would recommend a coat of oil be applied perhaps once or twice a year. It would also make good sense to provide both internal and external door matting in an effort to remove grit from the soles of your shoes, which may contribute to scratching of the surface, particularly in the winter months.

Should the floor become excessively soiled, OSMO offer a comprehensive range of cleaning products. i.e. the OSMO maintenance kit, where specific information regarding the cleaning of your oiled oak flooring can be found under the heading 'Normal cleaning and maintenance in private households'.

Further details on the full range of OSMO products including additional tips for the preparation and maintenance of your floor can also be found at www.osmouk.com

Should you require further information on Xylo Flooring products please visit our web site at www.xyloflooring.com